

COMPACT, LIGHT WEIGHT DESIGN, 2 INCH PORTABLE PRINTER!

MOBILE PRINTER

LK-P21

- Light weight(240g with battery) & With robust durable structure
- Compact size : 80mm x 133mm x47mm (W x L x H)
- Lithium-ion rechargeable battery : 130M(about 1300 pieces) printable
- Prints at 80mm per second
- Dual headed MSR(Optional)
- Equipped power options DC charger and vehicle charger(12/24V)
- Various O/S drivers : Win CE/Mobile, Symbian, Linux, Blackberry



Made for
 iPod iPhone iPad



MSR



ACCESSORIES



CASE

CRADLE

STRAP

SPECIFICATION

ITEM	TYPE	
MODEL	LK-P21	
PRINTING	METHOD	Direct Thermal
	SPEED	80mm / sec
DOT DENSITY	203 DPI	
DOT PITCH	8dots /mm, 0.125 pitch	
CHARACTER PER LINE	Font A(12 x 24) 32 columns Font B(9 x 17) 42 columns	
PAPER	TYPE	Thermal Paper / Linerless(Optional)
	WIDTH	58mm
	THICKNESS	0.06mm ~ 0.09mm
	ROLL DIAMETER	Max. ø 40.0mm
RELIABILITY	ROLL CORE INNER	12.5mm ± 0.5mm
	TPH LIFE	50km
CHARACTER SET	IP	IP42 (Standard), IP54 (with Protective Case)
	ALPHA NUMERIC CHARACTER	95
BARCODE	EXTENDED GRAPHIC INTERNATIONAL CHARACTER	128 x 18page(1 space page) 14
	1D : EAN-8, EAN-13, Code39, ITF, UPC-A, UPC-E, Codabar, Code93, Code128	
EMULATION	ESC/POS, CPCL, ZPL Command compatible	
DRIVER	Windows Driver(10, 2012, 8, 7, 2008, VISTA, 2003, XP, 32bit & 64bit), Window CE & Mobile Driver & SDK (CE 4.2~, Mobile 5.0~), Linux Driver, Mac Driver, OPOS Driver, JavaPOS Driver, iOS SDK, Android(2.1~) SDK, Blackberry SDK, Symbian	
SENSOR	Paper end	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 1130mAh Li-ion, 2.2Hrs Charging Time, 19Hrs stand-by	
DIMENSION	80mm x 133mm x 47mm (W x D x H)	
WEIGHT	240g (With Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80%
	STORAGE	10 ~ 90%

